



6.5" Industry Touch Monitor

GHK-06IP-TC

FEATURES

- VGA (640 x 480) (700 cd/m2)
- VGA & DVI Signal Input
- 5 Wire Resistive Touch Screen (Optional)
- OSD Control on the Back Side
- DC 12V Power Input
- Support VESA Wall Mount and Embedded Mount



RoHS



6.5
Inch
TFT



IP65

PRODUCT SPECIFICATIONS

LCD	
Panel Type	AU LCD Panel (Optional)
Resolution (pixel)	640*480
Display Area (mm)	132.48(H)x99.36V
Brightness (nit)	700nit
Contrast Ratio	600:1
Colors	16.2M / 262k colors
View Angle (U/D/L/R)	70/70/80/80
Backlight Lifetime	50000hrs
OSD Control	Auto Menu Select (+,-) Exit On/Off
Touch Screen	
Type	5 Wire Resistive
Resolution(pixel)	4096*4096
Transmittance	>90%
Interface	
Signal Input	VGA+DVI (15 Pin D-sub/DVI-D Connector)
Touch Connectors	USB / RS232(Optional)
Power	
Power Input	DC-in 12V=4A (50~61HZ)-DC Jack (2.0mm)
Power Consumption	≤48W
Mechanical	
Material	Steel chassis
Mounting	Support VESA Wall Mount and Embedded Mount
Dimensions	181.0(H) x 135.0(V) x 44.1(D)
Environment	
Operating Temp	-30~80C°
Storage Temp	-30~80C°
Relative Humidity	10~90% @40C° Non-condensing without touch screen
Vibration	1G peak,5~500Hz(Random)
Shock	15G peak acceleration (11msec.duration)
Rating	Facilitate installation of the demolition, solid portfolio
Ordering Information	
GHK-06IP-NC	6.5"Industry Monitor with VGA/DVI input and power adapter (640*480 / 700nit)
GHK-06IP-TC	6.5"Industry Touch Monitor with 5wire resistive touch screen,VGA/DVI input (640*480 / 700nit)

DIMENSIONS

