



# 8.4" Industry Touch Monitor

## GHK-08IP-TC

### FEATURES

- SVGA (800 x 600) (450 cd/m2)
- VGA & DVI Signal Input
- 5 Wire Resistive Touch Screen (Optional)
- OSD Control on the Back Side
- DC 12V Power Input
- Support VESA Wall Mount and Embedded Mount



RoHS



8.4  
Inch  
TFT



IP65

## PRODUCT SPECIFICATIONS

LCD	
Panel Type	AU LCD Panel (Optional)
Resolution (pixel)	800*600
Display Area (mm)	170.04(H)x127.8(V)
Brightness (nit)	450nit (Optional)
Contrast Ratio	600:1
Colors	16.2M / 252k colors
View Angle (U/D/L/R)	80/60/80/80
Backlight Lifetime	50000hrs
OSD Control	Auto Menu Select (+,-) Exit On/Off
Touch Screen	
Type	5 Wire Resistive
Resolution(pixel)	4096*4096
Transmittance	>90%
Interface	
Signal Input	VGA+DVI ( 15 Pin D-sub/DVI-D Connector )
Touch Connectors	USB / RS232(Optional)
Power	
Power Input	DC-in 12V=4A (50~61HZ)-DC Jack (2.0mm) & 3-PIN Industrial Connectors
Power Consumption	≤48W
Mechanical	
Material	Steel chassis
Mounting	Support VESA Wall Mount and Embedded Mount
Dimensions	226.5(H) x 161.0(V) x 38.2(D)
Environment	
Operating Temp	-30~80C°
Storage Temp	-30~80C°
Relative Humidity	10~90% @40C° Non-condensing without touch screen
Vibration	1G peak,5~500Hz(Random)
Shock	15G peak acceleration (11msec.duration)
Rating	Facilitate installation of the demolition, solid portfolio
Ordering Information	
GHK-08IP-NC	8.4"Industry Monitor with VGA/DVI input and power adapter (800*600 / 250nit)
GHK-08IP-TC	8.4"Industry Touch Monitor with 5wire resistive touch screen,VGA/DVI input (800*600 / 450nit)

## DIMENSIONS

