



15" Industry Monitor

GHK-15IP-NC

FEATURES

- SVGA (1024 x 768) (250 cd/m²)
- VGA & DVI Signal Input
- OSD Control on the Back Side
- DC 12V Power Input
- Support VESA Wall Mount and Embedded Mount



RoHS



15 inch
TFT



IP65

PRODUCT SPECIFICATIONS

| LCD | |
|----------------------|---|
| Panel Type | AU LCD Panel (Optional) |
| Resolution (pixel) | 1024*768 |
| Display Area (mm) | 304.128(H)x228.096(V) |
| Brightness (nit) | 250nit (Optional) |
| Contrast Ratio | 700:1 |
| Colors | 16.2M |
| View Angle (U/D/L/R) | 65/60/70/70 |
| Backlight Lifetime | 50000hrs |
| OSD Control | Auto Menu Select (+,-) Exit On/Off |
| Touch Screen | |
| Type | NO |
| Resolution(pixel) | NO |
| Transmittance | NO |
| Interface | |
| Signal Input | VGA+DVI (15 Pin D-sub/DVI-D Connector) |
| Touch Connectors | USB / RS232(Optional) |
| Power | |
| Power Input | DC-in 12V=4A (50~61HZ)-DC Jack (2.0mm) & 3-PIN Industrial Connectors |
| Power Consumption | ≤48W |
| Mechanical | |
| Material | Steel chassis |
| Mounting | Support VESA Wall Mount and Embedded Mount |
| Dimensions | 360.0(H) x 280.0(V) x 52.0(D) |
| Environment | |
| Operating Temp | 0~65C° |
| Storage Temp | -20~65C° |
| Relative Humidity | 10~90% @40C° Non-condensing without touch screen |
| Vibration | 1G peak,5~500Hz(Random) |
| Shock | 15G peak acceleration (11msec.duration) |
| Rating | Facilitate installation of the demolition, solid portfolio |
| Ordering Information | |
| GHK-15IP-NC | 15"Industry Monitor with VGA/DVI input and power adapter |
| GHK-15IP-TC | 15"Industry Touch Monitor with 5wire resistive touch screen,VGA/DVI input |

DIMENSIONS

